

# WCB Steel

## Straightway Stop Check

**Model #30SSC**

**Class 300 (3" to 8")**

**FEATURES:**

- These valves comply with applicable requirements of Section 1, Power Boilers, ASME Boiler and Pressure Vessel Code
- CA-15 seat and disc with stellite overlay, CA-15 stem and 304 SS disc guide for longer service life
- Hammer blow handwheel for 6" and larger valves

**Designed to ANSI B16.34,  
tested to API 598.  
Flanges to ANSI B16.5**



NO.	PART NAME	MATERIAL
1	BODY	A 216-WCB
2	SEAT	CA-15+ST6
3	DISC	CA-15+ST6
4	DISC GUIDE	A 351-CF8
5	PISTON RING	SPRING STEEL
6	BACK SEAT BUSH	A 276-304
7	STEM	A 479-410-1
8	SW GASKET	SS 316+GRAPHITE
9	BONNET	A 216-WCB
10	STUD	A 193-B7
11	HEAVY HEX NUT	A 194-2H
12	GLAND PACKING	GRAPHITE WITH INCONEL
13	STUD	A 193-B7
14	HEAVY HEX NUT	A 194-2H
15	GLAND FLANGE	A 216-WCB
16	STEM NUT	AL BRONZE (B 148-Gr D)
17	HANDWHEEL	A 216-WCB
18	HAMMER	A 216-WCB
19	WASHER	A 276-304
20	NYLOCK NUT	A 276-304
21	NPT PLUG	A 276-304

SIZE	INCH	3	4	6	8
	MM		80	100	150
A	INCH	14.75	17.00	21.50	26.00
	MM	374.7	431.8	546.1	660.4
B	INCH	10.0	14.0	18.0	20.0
	MM	254	356	457	508
C	INCH	18.0	22.5	28.1	32.0
	MM	457	572	714	813

